

# Hamilton Drywall Products



## Adhesives, Sealants and Caulks

### FORMULA #38

#### Drywall Construction Adhesive

Flexible, waterproof, synthetic rubber and resin base formula bonds drywall to wood or metal studs, concrete or block walls. Cures to a tough, rubbery stage



Prod#	Size	Tubes/Ctn	Units/Pallet	Unit	Wt/Unit
54010	28 oz. Tube	12	60	CTN	30

#### Specifications:

- Tested in accordance with ASTM E72-77 for racking and shear
- Tested per ASTM E-84, Surface Burning Characteristics
- Meets ASTM C-557-73

### SC-175

#### Sound Sealant

A non-flammable, water-base sealant specially designed for the reduction of sound transmission on wall and partition systems. Non-hardening, non-staining, freeze-thaw stable.



Prod#	Size	Tubes/Ctn	Units/Pallet	Unit	Wt/Unit
54020	28 oz. Tube	12	60	CTN	42

#### Specifications:

- UL Classified - 48S9 (R9732)
- Tested in accordance with and conforms to - UL723; U.B.C. Standard No. 42-1 Class I; ASTM E84: Surface Burning Characteristics of Building Materials
- ASTM E-90-85: Laboratory Measurement of Airborne-Sound Transmission Loss
- ASTM D217-73: Testing Standard for Consistency
- ASTM C919-79: Standard Practice for Use of Sealants in Acoustical Applications

### SW-325

#### Shear & Drywall Adhesive

Pro-Series® SW-325 is a high performance latex-based construction adhesive designed for drywall applications and fabricating shear wall rated assemblies. This adhesive is non-flammable, environmentally safe and VOC compliant for all interior and in-plant construction use.



Prod#	Size	Tubes/Ctn	Ctns/Pallet	Unit	Wt/Unit
54025	28 oz. Tube	12	60	CTN	30


#### Specifications:

- Tested per ASTM E72, Section 14. Racking Load Evaluation of Sheathing Materials on a Standard Wood Frame.
- Conforms to the performance characteristics of ASTM C557.
- Meets California's low VOC requirements for adhesives.
- SCAQMD Rule 1168 VOC; CARB; and BAAQMD complaint

### FRP-555

#### Latex FRP Panel Adhesive

A high quality, solvent free adhesive for installing fiberglass reinforced panels on common surfaces. Bonds to drywall, wood, concrete, metals, plastic, plastic foams, etc. Long open time with strong yet flexible bond. Nonflammable. Water-resistant.



Prod#	Size	Units/Pallet	Unit	Wt/Unit
54082	3.5 Gallon	24	PL	42
54085	5 Gallon	24	PL	63

#### Specifications:

- Meets SCAQMD Rule 1168 VOC
- CARB and BAAQMD compliant

### SALES/ORDER INFORMATION

P: (360) 225-6888 • P: (877) 443-7683 • Main Fax: (800) 871-5007 • CS Fax: (877) 5-FAX-HDP  
295 North Pekin Road • Woodland, Washington 98674 • www.hamiltonnw.com

Adhesives, Caulks, Mesh